

METAL PLATE  
EMBOSSER



## C430

Metal Plate Embosser

**Matica C430 electronic embosser has been specifically engineered for heavy duty and continous production. It is a strong, reliable system ready to emboss plates in the most harsh environments and can handle a huge variety of size, materials, shapes and thicknesses.**

The C430 comes equipped with an integrated, manually adjustable automatic plate feeder that holds up to 350 plates (0.5 mm thickness). The C430 is particularly suited for continuous medium to high volume production process. The system can easily accomodate various sizes and shapes of plates and can be efficiently used to emboss different identification plates within the same production facility.

Matica C430 provides a heavy duty embossing mechanism which includes a powerful high torque motor, high percussion embossing arm, hardened drum and fonts for the hardest jobs. The C430 is designed for the personalization of plates of various materials and thicknesses, including steel, iron, aluminium, bronze and can guarantee in all cases outstanding quality.

Once embossed, plates can either be placed in an external collection box via a side eject mechanism or stacked in a FIFO output stacker. The external tray is designed for those jobs where plate shape or side frequently changes. Matica C430 incorporates the Xon Xoff protocol and is compatible with Windows Generic printer driver. Production can be easily managed by any Windows based application. Other protocols are available. Data entry can alternatively be performed through a keyboard using the integrated sophisticated off-line editor.

- Renewed and modern design
- Ideal for medium to highvolumes
- Heavy duty embossing mechanism
- Variable plate and font size
- Manageable on-line and off-line

C430



# C430

Metal Plate Embosser

## TECHNICAL SPECIFICATIONS

<b>Productivity</b>	200 plates/hours (40 ch/plate) Recommended operating time: 16 hours/day
<b>Plate Handling</b>	Input hopper capacity: 350 plates (0.5 mm thickness) Input hopper height: 180 mm Side Eject or optional automatic variable FIFO output stacker Plate thickness: from 0.4 to 0.9 mm
<b>Plate Personalization</b>	Minimum plate dimensions (L x W): 50 mm x 20 mm Maximum plate dimensions (L x W): 120 mm x 90 mm Non - embossing area: 4mm from clamp side
<b>Embossing Drum</b>	Embossing drum: 100 characters (special drums available upon request)
<b>Available Characters</b>	Simplex 2 (350) - 3 mm embosser USA Block (490) - 4 mm Block (488) - 5 mm Double Block (511) - 6 mm (50 characters drum) Double Long Block (611) - 8 mm (50 characters drum) Maxi Block (711) - 12 mm (50 characters drum) Other fonts available on request All fonts are available in Standard or Reverse version
<b>Interface</b>	USB interface (USBtoCom driver) Protocol: Xon/Xoff, CHIP, L2, ##, SEP, Multi Embosser Storable format layouts: 2 of 50 fields x 80 characters RS232 serial port optional LAN optional PS2 Keyboard Interface (keyboard not included)
<b>Other Features</b>	Key-lock security feature LCD display (40 x 2) + 1 Clear button Emergency Stop button
<b>Warranty</b>	1 year or 500.000 plates
<b>Dimension (L x W x H)</b>	91 x 60 x 42 cm
<b>Weight</b>	Weight: 70 Kg
<b>Electrical Requirements</b>	Power Supply: 100 to 240 VAC; 50/60 Hz, 200 Watt
<b>Operating environment</b>	Temperature: 5 ÷ 40 °C Humidity: 30% ÷ 90% non condensing



- Military & Aerospace
- Steel & Metal Treatment Plants
- Automotive
- Electric Motors & Pump
- Shipyards

Authorized Reseller / System Integrator